



HOS CENTERLINE

370MPSV Multi-Purpose Service Vessel



DIMENSIONS AND REGULATORY INFORMATION

| | | | | | |
|-------------------------|---|--------------|---------------------|-------------------|-------------------------|
| Length: | 381 ft 0 in (116.1 m) | Beam: | 72 ft 0 in (21.9 m) | Draft Max: | 19 ft 1 1/2 in (5.83 m) |
| Gross: | 5,960 GT | Net: | 2,436 NT | Draft Min: | 11 ft 6 in (3.51 m) |
| IMO: | 9040546 | O.N.: | 981472 | Flag: | U.S. |
| Certifications: | Oceans-SOLAS, OSRV, SIP, USCG Subchapter D/O, USCG Subchapter I/L | | | | |
| Classifications: | Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, +AMS, ACC, ESP, Oil Carrier/Chemical Carrier/OSV, UWILD, CRC | | | | |

PERFORMANCE

| | | | | | |
|----------------------|---------|-----------------------|--------------------|----------|-------------------------|
| Cruise Speed: | 9.5 kts | 190 gal/hr (719 l/hr) | Max Speed: | 11.5 kts | 280 gal/hr (1,060 l/hr) |
| On DP: | | 105 gal/hr (397 l/hr) | On Standby: | | 60 gal/hr (227 l/hr) |

PROPULSION, MACHINERY AND STEERING

| | | | |
|----------------------------|--|--------------------------|--------------------|
| Main Engines: | 4 x Caterpillar 3516C | Total Rating: | 8,400 kW |
| Primary Generators: | 3 x Caterpillar C 18 | Total Rating: | 1,275 kW |
| Main Propulsion: | 2 x Rolls Royce Marine FPP Steerable | Total Rating: | 6,000 hp |
| Fwd Bow Thruster: | 1 x Rolls Royce Marine CPP Tunnel | Total Rating: | 1,500 hp |
| Aft Bow Thruster: | 2 x Rolls Royce Marine CPP Drop Down Azimuth | Total Rating: | 3,000 hp |
| Stern Thruster: | 1 x Rolls Royce Marine CPP Tunnel | Total Rating: | 1,500 hp |
| | | Power Generation: | 480V/60 Hz/3-Phase |

CAPACITIES AND DELIVERY RATES

| | | | |
|-------------------------|--|--------------------------|---|
| Deadweight: | 7,903 LT (8,029 MT) | Deck Area: | 200 ft x 58 ft (11,600 ft ²) 61.0 m x 17.7 m (1,077.6 m ²) |
| Deck Cargo: | 4,700 LT (4,775 MT) | Deck Load Rating: | 1,024 lbs/ft ² (5 MT/m ²) |
| Brine: | 30,961 bbl (4,922 m ³) | Discharge Rate: | 1,000 GPM (227 m ³ /hr) |
| Cargo Oil (D/O): | 24,547 bbl (3,902 m ³) | Discharge Rate: | 1,000 GPM (227 m ³ /hr) |
| Fresh Water: | 64,979 gal (246 m ³) | Discharge Rate: | 1,000 GPM (227 m ³ /hr) |
| Liquid Mud: | 30,961 bbl (4,922 m ³) | Discharge Rate: | 1,000 GPM (227 m ³ /hr) |
| Rig Fuel (I/L): | 36,274 bbl (5,766 m ³) | Discharge Rate: | 1,000 GPM (227 m ³ /hr) |
| Rig Water: | 32,210 bbl (5,120 m ³) | Discharge Rate: | 750 GPM (170 m ³ /hr) |
| Cooler Area: | 850 ft ³ (24 m ³) | Freezer Area: | 850 ft ³ (24 m ³) |

ELECTRONICS

Auto Pilot, CCTV Cameras, Cyscan, Depth Sounder, DGPS, EPIRB, Gyro Compass, Joystick Control, L-3 NMS 6000, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radar (S-band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar, VSAT

ACCOMMODATIONS

18 air conditioned/heated staterooms for 47 person(s) berthing total. The rooms are configured as follows:

- 2 air-conditioned staterooms for 1 person(s) berthing each.
- 9 air-conditioned staterooms for 2 person(s) berthing each.
- 1 air-conditioned staterooms for 3 person(s) berthing each.
- 6 air-conditioned staterooms for 4 person(s) berthing each.

Accommodations include : Client Office, Lounge

Capable of installing additional deck berthing for 31 person(s).

SPECIAL FEATURES

| | | | |
|-------------------------|-------------------------|-------------------------------|---------------|
| Stores Crane: | 3 x Hydra Pro HP70/20T | Max Lift @ Max Radius: | 2 MT @ 70 ft |
| | | Max Lift @ Min Radius: | 20 MT @ 10 ft |
| Roll Damping: | Anti-Roll Tank, Passive | | |
| Watermaker Cap.: | 9,000 USG/day | | |

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.